



THE GILMAN BROTHERS COMPANY

# INFINITY®

## SPECIFICATIONS

Physical Product Specifications	3mm"	3/16"	1/2"
<b>Target Thickness</b>	.118	.195	.500
<b>Thickness Tolerance</b>	+ / - .010	+ / - .010	+ / - .030
<b>Foam Core</b>	High density extruded polystyrene	High density extruded polystyrene	Welded high density extruded polystyrene
<b>Face Sheet Liners</b>	High impact polystyrene .012 print grade	High impact polystyrene .012 print grade	High impact polystyrene .012 or .015 print grade
<b>Diagonal Squareness</b>	1/8" or less	1/8" or less	1/8" or less
<b>Width</b>	+ / - 1/16"	+ / - 1/16"	+ / - 1/16"
<b>Length</b>	+ / - 1/16"	+ / - 1/16"	+ / - 1/16"
<b>*Warpage/*Bow</b>	1/16" per foot	1/16" per foot	1/32" per foot
<b>Cutting</b>	Razor, guillotine, die, saw, CNC cutters (Zund)	Razor, guillotine, die, saw, CNC cutters (Zund)	Razor, guillotine, die, saw, CNC cutters (Zund)

*\*All plastic constructed foam boards perform best if subjected to uniform temperatures on each board face.*