



Resilient[®]

Soft Touch Graphics Board

Frequently Asked Questions

1. **Can Resilient[®] be used for sound proofing applications?**
 - a. Currently no; formal testing is pending.
2. **Can I purchase just the core, without facers?**
 - a. Yes, on a case-by-case basis.
3. **Can the product be purchased in cartons?**
 - a. Yes, Resilient[®] will be available in cartons within 30-60 days.
4. **Is the product available in white or other colors?**
 - a. Not yet, but we are working toward providing other color core options.
5. **What is the fire rating on Resilient[®]?**
 - a. This product in nature is highly flammable. Formal testing is pending.
6. **What glue/adhesive can be used to adhere Resilient[®] to itself?**
 - a. We recommend hot melt EVAs or solvent-based urethane adhesives.
 - b. Example: 3M[™] Super 77[™] Multipurpose Spray Adhesive
7. **How can I cut Resilient[®]?**
 - a. Please see cutting guidelines on our website – [Resilient Cutting Guidelines](#).
8. **What is the best adhesive tape to mount Resilient[®] to walls?**
 - a. We recommend gel tape/Nano Tape. 3M Command[™] strips are safe to use depending on size and wall texture.
9. **Is Resilient[®] available in thinner gauges?**
 - a. Thinnest commercially available is 1/2" at this time.
10. **Can you produce Resilient[®] with different surfaces?**
 - a. Yes, as a making SKU. Please reach out to your BDL for details and MOQs.
11. **Is Resilient[®] waterproof?**
 - a. Yes, with standard styrene facers only. Different surfaces may alter this feature.
12. **Is Resilient[®] recyclable?**
 - a. No.